

TITLE OF THE INVENTION

IMAGE FORMING APPARATUS HAVING A PLURALITY OF  
SHEET STACKING MEANS

5

BACKGROUND OF THE INVENTION

Field of the Invention

10 The present invention relates to an image forming  
apparatus in which sheets are discharged into any one of a  
plurality of sheet stacking means.

Description of the Related Art

15 There has been proposed a discharging option for a  
printer in which movable discharging bins have only one  
sensor for detecting the amount of paper stacked in each  
discharging bin and the detection is performed by a move of  
each discharging bin. In addition, a control method for a  
printer connected to the discharging option has been  
proposed. In this control method, a print instruction is  
20 received from a host computer and command analyzing is  
performed, whereby it is determined whether to start  
printing based on previously-obtained discharging-bin  
information regardless of the present state of the  
discharging bin information in accordance with feeding and  
25 discharging commands obtained by the analysis.

The above-described conventional examples have the following problems:

In the printer, only while actual feeding and discharging is being performed, the condition of the discharging bin in use can be detected. If the discharging bin is already full when the print instruction is received, several sheets are still printed because the detection of the stacked-paper amount is performed during actual discharging. Accordingly, the several sheets are discharged into the fully-stacked discharging bin before a notification of the full stack is issued. In other words, if the discharging bin is changed by a discharging-bin selecting instruction transmitted as part of print data from the host computer, the stacked-paper amount in the selected discharging bin cannot be detected until the previous sheets are discharged by performing the next printing because a discharging bin into which the previous discharging was performed has been operational (in a condition capable of detecting the stacked-paper amount). Accordingly, the processing must be performed based on the previous information. In the case of a discharging system with one single sensor that can detect only the stacked-paper amount of the operational discharging bin, detection is impossible when a user removes or puts paper in a discharging bin other than the operational discharging bin, namely, interference

occurs, and the system cannot operate based on accurate information because only the paper-stacked amount can be detected.

As described above, after discharging is started, an accurate stacked-paper amount can be detected. Thus, a discharging bin that has already been full may be used as the selected discharging bin. Thus, sheets are discharged into the fully-stacked discharging bin, and paper jamming occurs in the discharging system, which often causes malfunctioning.

In the case where paper in the fully-stacked discharging bin, which is not operational, is removed by the user, a problem occurs in that the discharging system has determined that the stack is full, and prohibits the discharging bin from being used despite the fact that paper can be practically stacked in the discharging bin.

In the case where the discharging system has two modes: an automatic discharging mode for discharging into an empty discharging bin, and a fixed discharging mode for discharging into one fixed discharging bin, the modes may be mixed when being used by a plurality of users in a network environment. If, in the automatic discharging mode, a user performs a job that needs discharging a large amount of paper, the paper may be discharged into a plurality of discharging bins. By way of example, in the case where a

user A performs fixed outputting to a second discharging bin,  
and another user B uses the automatic discharging mode to  
perform large-amount outputting to a first discharging bin  
as a starting point, the output of user B is discharged into  
5 the second discharging bin after the first discharging bin  
is full. Thus, the output of user B is stacked on the  
output of user A. The output of user A is mixed in the  
output of user B. Therefore, the user B who does not know  
that the output of user A has been discharged into the  
10 second discharging bin may mistakenly remove the output of  
user A.

#### SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention  
15 to provide an image forming apparatus in which the foregoing  
problems are solved.

To this end, according to an aspect of the present  
invention, the foregoing object has been achieved through  
provision of an image forming apparatus comprising: image  
20 forming means for forming images on sheets; a plurality of  
sheet stacking means in which the sheets are stacked;  
selector means for selecting one sheet stacking means;  
moving means for moving to a predetermined position the  
sheet stacking means selected in accordance with the  
25 selection by the selector means; detection means for

detecting the sheet-stacked condition of the selected sheet  
stacking means at the predetermined position; and control  
means performing control so that, when one sheet stacking  
means is changed, the moving means moves the sheet stacking  
5 means, and after the detection means detects the sheet-  
stacked condition of the sheet stacking means, image  
formation by the image forming means is started.

According to another aspect of the present invention,  
the foregoing object has been achieved through provision of  
10 an image forming apparatus comprising: image forming means  
for forming images on sheets; a plurality of sheet stacking  
means for stacking the sheets; control means for activating  
a first mode for stacking the sheets by the sheet stacking  
means specified by an external unit, and a second mode for  
15 stacking the sheets by the sheet stacking means  
automatically selected by the image forming apparatus; and  
information means used such that, in the second mode, when  
the sheet stacking means is changed, the information means  
gives information urging sheet removing in accordance with  
20 the sheet-stacked condition of the changed sheet stacking  
means.

According to a further aspect of the present invention,  
the foregoing object has been achieved through provision of  
a stacker comprising: stacking means for stacking sheets on  
25 which images are formed; discharging control means for

performing either of face-down discharging and face-up  
discharging onto the stacking means; detection means for  
detecting the amount of the sheets stacked on the stacking  
means; and full-stack detecting means for detecting a full  
5 stack in accordance with a first amount of the stacked  
sheets detected by the detection means when the face-down  
discharging is performed by the discharging control means,  
and detecting a full stack in accordance with a second  
amount of the stacked sheets, which is less than the first  
10 amount of the stacked sheets, detected by the detection  
means.

Other objects and features of the present invention  
will be apparent from the following description and the  
attached drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram illustrating an image forming  
apparatus.

20 Fig. 2 is a schematic section view illustrating an  
image recording system composed of an image forming  
apparatus and its option units.

Fig. 3 is a block diagram illustrating interfaces for  
the controllers in the image recording system shown in Fig.  
25 2.

Fig. 4 is a block diagram illustrating details of the video controller shown in Fig. 1.

Fig. 5 is a schematic diagram showing a shared memory for the video controller 103 and the option controller 106 shown in Fig. 1, which is reserved in a random access memory provided in the option controller 106.

Fig. 6 is a flowchart showing one example of a process for obtaining option information via an option controller.

Fig. 7 is a flowchart showing a scheduling task.

Fig. 8 is a flowchart showing an engine interface (I/F) task.

Fig. 9 is a flowchart showing an option I/F task.

Fig. 10 is a flowchart showing a process for notifying a user of a paper feeding-and-discharging system in remote control from panel operation and a host computer.

Fig. 11A is a schematic chart showing a procedure in which a command status is issued based on a basic status to obtain detailed information on each input option. Fig. 11B is a schematic chart showing a procedure in which a command status is issued based on a basic status to obtain detailed information on each output option.

Fig. 12 is a flowchart showing a scheduling task.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 shows a system structure including a printer

such as a laser beam printer. In this embodiment, the included printer is not limited to the laser beam printer, but may be other types of printer such as an ink-jet printer. One embodiment in which two option units are connected to the system is described below with reference to the attached drawings. However, more option units can be connected, and the system itself may have the function of each option unit.

In Fig. 1, a laser beam printer 102 can be connected to various option units such as a finisher and a paper deck, and is connected to an external unit 101 by a general-purpose interface (e.g., Centronics, RS-232C, etc.). The laser beam printer 102 performs image recording based on print information (control information such as code data based on a predetermined printer language including, e.g., Postscript, LIPS III, LIPS IV, and image data) transferred from the external unit 101 via the general-purpose interface. A video controller 103 is connected to the external unit 101 by the general-purpose interface. The video controller 103 receives code data (ESC code, types of PDL data, etc.) transferred from the external unit 101 via the general-purpose interface, and generates page information composed of dot data etc. based on the code data. The video controller 103 transmits (binary or multivalued) image data to an engine controller 105 (described below) via a video interface 80, and transmits a feeder selecting command,



discharger selecting command, etc. to an option controller 106 (described below) via a total interface 90. The engine controller 105 uses a known photographic process to form a latent image on a photosensitive drum based on the image data transferred from the video controller 103, and performs printing by transferring and fixing the latent image on a sheet of paper supplied. At this time, the engine controller 105 uses the video controller 103 to notify the option controller 106 of timing for paper feeding and discharging.

A panel unit 104 consists of various switches (buttons) for operations, light-emitting-diode indicators, and liquid-crystal display devices. The panel unit 104 is used as an interface with a user. The user can command the printer 102 to perform a predetermined operation by operating the panel unit 104. Various data etc. set by the user are stored and managed in non-volatile memories (such as an NVRAM and an EEPROM) in a control unit 109. The option controller 106 is a total controller that includes a CPU, a ROM and a RAM (not shown) and that completely controls at least one option unit based on an instruction for feeding and discharging paper transferred from the video controller 103 and an instruction for paper feeding-and-discharging timing transferred from the engine controller 105. The option controller 106 performs communication with an option controller unit

provided for each option unit via an option-unit interface 70, whereby totally controlling each option unit.

The RAM of the option controller 106 includes a shared memory that can be accessed by the video controller 103. As shown in Fig. 5, the shared memory includes a carrying-condition management area for 40 pages, a basic status area, a command-and-status management area, and an activation processing area. The video controller 103 directs each option unit via each area in the shared memory.

The carrying-condition management area consists of a region for notifying each option unit of instructions (feeder, discharger, color, stapling, shift discharging, etc.) in units of sheets of paper, and a region for notifying the video controller 103 of each option condition (to what extent printing has been performed, discharging completed, etc.). The basic status area is a region for notifying the video controller 103 of abnormal conditions (paper jam, paperless stapling, no staples, etc.) in each option unit. The command-and-status management area is a region for an exchange of commands and statuses with the video controller 103. The activation processing area is a region for instructing by the video controller 103, activation processing for each option unit.

A feeding option unit 107 (shown in Fig. 1) is, for example, a paper-deck option unit, and includes a paper-deck

controller (large-capacity feeding controller) 107a, whereby paper feeding is controlled based on control information transmitted from the option controller 106. The paper-deck controller 107a includes a CPU, a ROM, and a RAM (not shown), and the CPU controls the feeding option unit 107 based on programs stored in the ROM. In the ROM, extension information as to the feeding option unit 107, for example, information as to paper sizes capable of being accommodated in the paper deck is stored.

A paper-discharging option unit 108 is, for example, a finisher option unit having a stapling function. The paper-discharging option unit 108 includes a finisher controller (large-capacity paper-discharging stacker controller) 108a, whereby stapling and discharging is performed based on control information transmitted from the option controller 106. The finisher controller 108a includes a CPU, a ROM, and a RAM (not shown), and the CPU controls the paper-discharging option unit 108 based on a program stored in the ROM. In the ROM, extension information as to the paper-discharging option unit 108 are stored, such as the number of discharging bins, whether a stapling function is provided, whether a shift function for shifting discharged paper in a predetermined direction is provided, and whether an inverting function for inverting the face direction of discharged paper is provided.

The feeding option unit (paper deck) 107 and the paper-discharging option unit (finisher) 108 are respectively provided with operation units 107b and 108b having a display unit and various keys, whereby, when each unit 107 or 108 is  
5 used, a message, an operation method, etc. can be displayed for the user, and the user can operate each unit 107 or 108.

The control unit 109 includes the engine controller 105 for performing print process control in the printer 102, the video controller 103 for performing total control of the  
10 printer 102 and analyzing and converting data from the external unit 101 such as a host computer into image data, and the option controller 106 for performing total control of the option units 107 and 108.

The option controller 106 uses the common option-unit  
15 interface 70 to manage the option units 107 and 108, and uses the total interface 90 to communicate with the video controller 103. In this embodiment, the option units 107 and 108 are controlled using the option controller 106 by the video controller 103.

20 Fig. 2 is a sectional view illustrating the structure of the laser beam printer 102 shown in Fig. 1, in which components identical to those shown in Fig. 1 are denoted by the same reference numerals. Referring to Fig. 2, a paper cassette 230 holds recording paper S, and has a mechanism  
25 for using the position of a partition to detect the size of

recording paper S. A cassette feeding clutch 231 is a cam that separates only one top sheet of the recording paper S loaded in the paper cassette 230 and carries the separated recording paper sheet S to a feeding roller 204. The  
5 cassette feeding clutch 231 intermittently rotates whenever feeding is performed, whereby one sheet of the recording paper S is fed so as to correspond to one rotation of the cassette feeding clutch 231. A recording-paper detecting sensor 230S detects the amount of the recording paper S in  
10 the paper cassette 230.

A resist shutter 227 presses the recording paper S to stop paper feeding. A feeding roller 204 carries the top portion of the sheet of the recording paper S to the resist shutter 227. Recording paper S is disposed on a manual-  
15 feeding tray 202. A manual feeding clutch 203 carries the recording paper S disposed on the manual feeding tray 202 to the resist shutter 227. An option feeding roller (feeding relay roller) 233 supplies to the inside of the printer 102 the recording paper S fed from the feeding option unit 107.

20 A pair of resist rollers 205 that performs the synchronized carrying of the recording paper S is provided after the manual feeding clutch 203, the cassette feeding clutch 231, and the option feeding roller 233. An image recording unit 207 that uses a laser beam emitted from a  
25 laser scanner unit 206 to form a toner image on one sheet of

the recording paper S by using a known electrographic process is provided above the pair of resist rollers 205.

5 In the laser scanner unit 206, a laser unit 215 emits a laser beam based on an image signal (VDO signal) sent from the video controller 103. A polygon mirror 216 causes the laser beam emitted from the laser unit 215 to scan a photosensitive drum 220 via an imaging lens unit 218 and a turn mirror 219, whereby the latent image is formed on the photosensitive drum 220. A beam detector 217 detects the laser beam emitted from the laser unit 215 before outputting a main-scanning synchronizing signal. A luminous amount sensor 270 detects the luminous amount of the laser beam emitted from the laser unit 215.

15 In the image recording unit 207, a primary charger 222 uniformly charges the photosensitive drum 220. A developer 223 is charged by the primary charger 222, whereby the latent image formed on the photosensitive drum 220 as a result of laser exposure by the laser scanner unit 215 is developed with toner. A transfer charger 224 transfers the toner image developed by the developer 223 onto the sheet of recording paper S fed by the resist roller 205. A cleaner 225 removes the remaining toner. A pre-exposure lamp 221 discharges the photosensitive drum 220 with its light.

25 A fixer 208 uses heat to fix on the sheet of recording paper S the toner image formed by the image recording unit

207. A carrier roller 210 discharges the sheet of recording paper S. A discharging sensor 209 detects the condition of discharging. A flapper 211 turns the discharging direction of the sheet of recording paper S on which recording is complete to the discharging tray 213 or the paper-discharging option unit 108. Discharging rollers 214 and 212 discharge the sheet of recording paper S carried by turning the flapper 211 onto a stacker tray 213. A discharged-paper-amount detecting sensor 213s detects the amount of the recording paper S stacked on the stacker tray.

The engine controller 105 in the control unit 109 controls the electrographic process using the laser scanner 206, the image recording unit 207 and the fixer 208, and controls the carrying of the recording paper S in the laser beam printer 102.

The video controller 103 is connected to the external unit such as a personal computer by the general-purpose interface (e.g., Centronics, RS-232C, etc.). The video controller 103 expands image information sent via the general-purpose interface into bit data, and sends the bits data as a VDO signal to the engine controller 105 via the video interface 80.

Next, each option unit removably connected to the laser beam printer 102 will be described. The option controller 106 (shown in Fig. 1) is provided in the laser beam printer

102, and can perform communication using the same protocol via the option-unit interface 70 as a common bus for each option unit. The option controller 106 is connected to the video controller 103 via the total interface 90.

5        In the feeding option unit 107 as a paper-deck option unit, a large amount of the recording paper S is stored on a paper deck 241 as an elevator. A paper-deck feeding roller 242 feeds the recording paper S. Carrier rollers 244 carry the recording paper S fed by the paper deck feeding roller  
10       242 toward option feeding rollers 233. Feeding relay rollers 243 relay the recording paper S fed from other feeding option units (capable of feeding the recording paper S having a different size or the same size) that can be removably connected to the bottom of the feeding option 107.  
15       The paper deck 241 also detects the amount of the stacked recording paper S. The paper-deck option unit 107 is controlled by the paper-deck controller 107a.

      In the discharging option 108 as a finisher option unit, recorded sheets of the recording paper S are separately  
20       stacked by a first discharging bin 251, a second discharging bin 252, and a third discharging bin 253. A bin lifting motor 260 vertically moves the discharging bins 251 to 253 to change the discharging direction. For the sheet of the recording paper S that was distributed by the flapper 211  
25       before being sent to the finisher option unit 108, carrying



is switched so that sheet face switching (either face-up or face-down) is performed based on an instruction from the video controller 103.

A discharged-paper-amount detecting sensor 261 detects  
5 the amount of the recording paper S discharged into the selected discharging bin. The discharged-paper-amount detecting sensor 261 is a height sensor that detects the height of the recording paper S stacked on the discharging bin by optically detecting the distance between it and the  
10 top sheet of the recording paper S. When the height of the recording paper S, stacked on one of the first discharging bin 251 to the third discharging bin 253, reaches a predetermined value, the finisher controller 108a uses the option controller 106 to notify the video controller 103 of  
15 the fully stacked condition. A standard for detecting a fully stacked condition in the face-down discharging mode is set at 88 mm (corresponding to approximately 700 sheets), a standard for detecting a fully stacked condition in the face-up discharging mode is set at 44 mm. This is because  
20 face-down discharged sheets are limited to sheets having preferable stackability, while face-up discharged sheets may be sheets having inferior stackability, such as envelopes, cardboard, and overhead-projector sheets. The reason why the face-down discharging is controlled so that envelopes,  
25 cardboard, and overhead-projector sheets are not discharged

is that such types of sheet may be jammed when being switched back, since switching back is required for the above-described face-down discharging. In addition, in a mode where stapled sheets are stacked, a standard for

5 detecting a fully stacked condition is set at 44 mm. In this embodiment, the amount of stacked sheets is detected by height detection. However, by counting the number of discharged sheets for detecting the amount of stacked sheets, the above-described control may be performed. In this case,  
10 a standard for detecting a fully stacked condition in the face-down discharging mode is set at 700 sheets, and a standard for detecting a fully stacked condition in the face-up discharging mode or the stapling mode is set at 350 sheets.

15 When the face-up discharging is commanded through the total interface 90 by the video controller 103, the sheet of recording paper S, distributed by a flapper 254, is carried to the discharging bin 251, 252 or 253. When face-down discharging is commanded through the total interface 90 by  
20 the video controller 103, the sheet of recording paper S, distributed by the flapper 254, is once carried by rollers 256 and 257 until the end of the sheet passes over the rollers 256, and the rollers 257 inversely rotate to carry the end of the sheet to rollers 258, and further to the  
25 discharging bin 251, 252 or 253.

When stapling is commanded through the total interface 90 by the video controller 103, a stapler 259 executes stapling before discharging the sheet of recording paper S to any one of the first discharging bin 251 to the third discharging bin 253. When shifting is commanded through the total interface 90 by the video controller 103, the first discharging bin 251 to the third discharging bin 253 are shifted, and the sheet of recording paper S is discharged into any one of the first discharging bin 251 to the third discharging bin 253. This shifts the stack region for the discharged sheet of recording paper S. A residual staple detecting sensor 259S detects the residual amount of staples in the stapler 259. The finisher option unit 108 is controlled by the finisher controller 108a.

The option controller 106, the paper-deck controller 107a, and the finisher controller 108a are connected by connectors, and use the option-unit interfaces 70 to perform serial communication. They are connected in series by the same connectors. Accordingly, the paper-deck controller 107a, and the finisher controller 108a can be permuted.

The pair of resist rollers 205, the feeding rollers 204, and the carrier rollers 244 are provided after the manual feeding roller 203, the cassette feeding clutch 231, and the paper deck feeding roller 242, respectively. The image recording unit 207 that uses the laser beam emitted from the

laser scanner 206 to form a toner image on a sheet of recording paper S is provided after the resist rollers 205. The fixer 208 that uses heat to fix the toner image formed on the sheet of recording paper S is provided after the image recording unit 207. The discharging sensor 209 for detecting the condition of carrying by the discharging unit, and the carrier rollers 210, and the flapper 211 for carrying the sheet of recording paper S are provided after the fixer 208.

Fig. 3 shows a block diagram of the laser beam printer 102 shown in Fig. 1, and components identical to those shown in Fig. 1 are denoted by the same reference numerals. Commands, such as a feeding instruction to the paper deck option unit 107 and a discharging bin instruction to the finisher option unit 108, are transmitted from the video controller 103 to the option controller 106 via a serial communication interface 91. Statuses, such as whether the paper deck option unit 107 has the recording paper S, how many the sheets of recording paper S are stacked on each discharging bin of the finisher option unit 108, and whether staples are left, are transmitted from the option controller 106 to the video controller 103 via the serial communication interface 91. The option controller 106 and the video controller 103 may be directly connected by a CPU bus.

An option ready signal (OPTRDY) signal 92 represents

whether or not an option specified by the video controller 103, for example, stapling can be used. The OPTRDY signal 92 is transmitted from the option controller 106 to the video controller 103. A paper-out timing (POUTT) signal 93 functions as a timing signal used when the laser beam printer 102 discharges the recording paper S. A paper-feed timing (PFEDT) signal 94 functions as a timing signal used when the laser beam printer 102 receives the recording paper S from the paper deck option unit 107. A speed change signal (SPCNG) signal 95 functions as a signal for reducing the speed of the sheet of recording paper S rapidly carried into the paper deck option unit 107 so as to be matched with a carrying speed used by the laser beam printer 102.

Commands, such as a feeding instruction to the feeding cassette in the laser beam printer 102, a discharging instruction to the discharging tray 213, and a print instruction, are sent from the video controller 103 to the engine controller 105 via a communication interface 81. Statuses, such as whether the paper cassette 230 in the laser beam printer 102 has the recording paper S, and paper jam, are sent from the engine controller 105 to the video controller 103. A VDO signal 52 represents bit data transmitted from the video controller 103.

The total interface 90 consists of five hardware signals: the serial communication interface 91; the OPTRDY

signal 92, the POUTT signal 93, the PFEDT signal 94 and the PCNG signal 95. The POUTT signal 93, the PFEDT signal 94, and the PCNG signal 95 are output from the engine controller 105, and are input to the option controller 106 via the video interface 80 and the video controller 103.

Fig. 4 is a block diagram illustrating the structure of the video controller 103 shown in Fig. 1. Components identical to those shown in Fig. 1 are denoted by the same reference numerals. A panel interface (I/F) 401 receives various settings and instructions by an operator from the panel unit 104 by performing data communication with the panel unit 104. A host interface (I/F) 402 is a signal input/output unit with the external unit such as a host computer. An engine interface (I/F) 406 is a signal input/output unit with the engine controller 105. The engine I/F 406 sends a data signal from its output buffer register (not shown), and controls communication with the engine controller 105.

An image data generator 403 generates bitmap data for actual printing based on control code data sent from the external unit 101. An image memory 405 stores image data. A CPU 409 controls the totality of the video controller 103. A ROM 404 stores control codes for the CPU 409. A RAM 407 functions as a temporary memory means used by the CPU 409. An electrically erasable programmable read-only memory

(EEPROM) 410 is composed of a non-volatile memory medium. A DMA controller 408 transfers bitmap data stored in the image memory to the engine interface 406 in accordance with an instruction from the CPU 409. An option interface (I/F) 412 communicates with the option controller 106 in accordance with an instruction from the CPU 409. The POUTT signal 93, the PFEDT signal 94, and the PCNG signal 95 are directly sent from the engine I/F 406 to the total interface 90.

A system bus 411 has an address bus and a data bus. The panel I/F 401, the host I/F 406, the image data generator 403, the ROM 404, the image memory 405, the engine I/F 406, the RAM 407, the DMA controller 408, the CPU 409, the EEPROM 410, and the option I/F 412 are connected to the system bus 411, and can access all function units on the system bus 411.

A control code for controlling the CPU 409 is composed of an operating system for using system clocks (not shown) to perform time-sharing control in units of loaded modules called "tasks", and loaded modules (shown below) operating in units of functions.

Fig. 5 is a schematic diagram showing a shared memory with the video controller 103, which is reserved in a RAM provided in the option controller 106. Figs. 11A and 11B are schematic charts showing procedures in which a command status is issued based on a basic status to obtain detailed

information on each option unit. Figs. 6, 7, 8, 9, and 10 are flowcharts illustrating this embodiment.

A control method in which the video controller 103 uses the option controller 106 to perform total control of each option unit is described with reference to Figs. 5, 11A and 11B. The shared memory, shown in Fig. 5, is composed of a carrying-condition management area for issuing an instruction on a page and knowing the sheet carrying condition, a basic status area for knowing abnormal conditions of each option unit, a command-and-status management area for exchanging command statuses, and an activating area for instructing the activation of each option unit.

The activating area is composed of an instruction part for sending an instruction from the video controller 103 and a completion notification part for reporting completion of processing by each option unit as a result of sending the instruction. The video controller 103 stores an instruction in the activating area to activate each option. When the main power is supplied, the video controller 103 notifies the activating area of an instruction for acquiring configuration information of each option unit, completion of information acquisition, etc. The completion notification part is monitored as to whether each processing is completed. The activation is terminated by recognizing the completion.



The carrying-condition management area is composed of an area for instructing printing conditions such as the feeding unit, the discharging unit, color/monochrome, stapling position, and executing, and an area used for the video controller 103 to report option condition. The video controller 103 specifies the printing conditions to execute printing, while knowing each option condition.

The above-described instructing can be performed for a maximum of 40 pages. The instructing is sequentially performed for each page. A region used for a page completely discharged is regarded as a space, and is initialized so as to be reused in the manner of a ring buffer.

The basic status area reports abnormal conditions of each option unit. From the basic status area, conditions, such as paper end, paper jam, panel open, and full stack, are acquired. From the contents of the basic status, more detailed information is acquired based on the command-and-status.

The command-and-status management area is for controlling the detailed information acquisition and operation of each option unit. By specifying a necessary command in this area, information is acquired. Information that can be acquired is, for example, a unit name, the size of a paper sheet to be fed, the amount of paper sheets left,

the position of paper jam, a type, an access point, the amount of discharged sheets of paper stacked, details of malfunction, and so forth. These particulars cause corresponding commands to be issued, and statuses are received in response. In addition, option controls, such as transfer to a power-saving mode, emergency stop at paper jam, a discharging bin move, and resetting, are performed using the command-and-status area.

As described above, the video controller 103 acquires the information. When no abnormal condition is detected, the video controller 103 executes printing. When an abnormal condition is detected from the basic status, the video controller 103 issues a command status for specifying an abnormal part, whereby further specifying an abnormal particular for the unit, and performs detailed information collecting and control in accordance with the abnormal condition.

Fig. 6 is a flowchart of processing in which the video controller 103 accesses the shared memory in the option controller 106 and issues command statuses with each option unit for information exchange.

For acquiring option information, the video controller 103 directs the command-and-status area in the memory of the option controller 106, and receives information. The video controller 103 specifies at predetermined addresses in the

command specified region a command ID by which the type of  
necessary information can be identified (step S601), the  
number of command data for using execution commands to  
direct the option controller 106 (step S602), and specifies  
5 data representing specified contents (step S603). The video  
controller 103 notifies the option controller 106 of its  
having transmitted commands, whereby triggering the  
acquisition of information from each option unit (step S604).  
Based on the given trigger and the specified contents, the  
10 option controller 106 obtains the specified information by  
performing serial communication with a specified option unit.  
In addition, a timer is activated until the option  
controller 106 completely obtains the information, and the  
process monitors whether the video controller 103 is in a  
15 condition capable of acquiring the status information (steps  
S605 and S606). In the case where transfer to a condition  
capable of acquiring the status information is not performed,  
after constant time passes, no status-information acquiring  
performs retry notification for re-executing the command  
20 (step S611) before the process ends. If, in step S602,  
transfer to the condition capable of acquiring the status  
information has been performed, the status ID is obtained to  
recognize whether the status information corresponds to the  
specified command (step S607). Next, with the number of  
25 status data obtained (step S608), status data for the number

of status data are obtained (step S609), and the option controller 106 is notified of completion of the status acquisition (step S610).

Fig. 7 is a flowchart of a scheduling task using  
5 command information analyzed and converted by a translating task to perform scheduling based on the control data and print data sent from the host computer 101. This scheduling task is executed by the video controller 103. In S701, the scheduling task monitors whether it receives data from which  
10 page control information and print information (sent from the host computer 101) should be created. When the scheduling task in the video controller 103 receives the print data from which page control information and print information should be created, it creates page control  
15 information and print information based on the contents specified by a layout command (step S702). Base on the page information created in step S702, a feeding-and-discharging system is determined (step S703). The reason why steps S702 and S703 are separately provided is that, in step S702, the  
20 instruction includes discharging-bin automatic selection, and in this step, a final feeding-and-discharging system cannot be determined. In other words, step S702 differs from step S703 in that a fixed feeding-and-discharging system is determined based on information such as paper end  
25 and a paper size for feeding, and whether stacking can be

performed for discharging.

Next, in accordance with the feeding-and-discharging system determined in step S703, the scheduling task determines whether bin moving is needed. In the case where the bin moving is needed, the scheduling task issues a bin moving command to the option controller 106 so that a discharging bin to which discharging is performed is operational, and the scheduling task detects operational-bin paper-stacking information etc (step S705). As a result of detecting the operational-bin paper-stacking information, when, in the discharging-bin automatic-selection mode, the discharged paper is stacked in the operational bin (step S706), a message such as "Remove paper" is displayed on the panel unit 104, and the host computer 101 is notified of the status, whereby the user is urged to remove the discharged paper (step S707), and paper removing is awaited. If, in step S706, the discharging-bin automatic-selection mode is not set, in other words, the fixed-bin-selection mode is set, or the discharged paper is not stacked, the scheduling task proceeds to step S708. The discharging-bin automatic-selection mode is such that discharging into the bin specified by the external unit 101 or a predetermined bin is performed, and the bin is automatically switched to another bin when being full. The fixed-bin-selection mode is such that fixed discharging into only the bin specified by the

external unit 101 is performed.

The reason why step S707 is executed is as follows:  
assuming that, when a print job in the discharging-bin  
automatic-selection mode is instructed, with paper from  
5 another job left in the second bin, discharging into the  
first to third bins has been performed because of a large  
number of print pages, a problem occurs in which all the  
paper in the first to third bins are removed by a user  
having instructed the print job in the discharging-bin  
10 automatic-selection mode, and the included other-job paper  
is removed by the different user. Conversely, in the fixed-  
bin-selection mode, a user removes a user's-job paper in a  
selected bin on condition that various users can select  
arbitrary bins. If other-job paper is in the selected bin,  
15 paper is discharged into the selected bin. When discharging  
can be performed, the scheduling task specifies printing in  
the shared memory (shown in Fig. 5) of the option controller  
106 via the option I/F task (step S708).

In step S709, the scheduling task determines whether  
20 there is a page on which printing has not been performed.  
If there is a page, the scheduling task determines whether  
the engine controller 105 is ready and is in a condition  
capable of sending print output (step S710). The scheduling  
task directs an engine I/F task (shown in Fig. 8 described  
25 below) to perform printing (step S711), and the engine I/F

task directs the engine controller 105 to perform printing, whereby printing is started. In steps S709 and S710, if there is no data to be printed and the engine controller 105 is not in a condition capable of sending print output, the  
5 scheduling task does not direct the engine I/F task, and the process proceeds to step S712.

In step S712, the scheduling task monitors whether completion of discharging has been received. If the completion of discharging has been received, the scheduling  
10 task updates the condition of the specified page so that the completed page information is eliminated to increase a memory capacity before the process returns to the receiving determination in step S701. In the case where, after print data for only one page is specified, print data for which  
15 scheduling should be performed is not sent, step S712 is repeatedly performed, whereby the scheduling task only updates the specified page. In the case where continuous printing is performed by receiving print data for a plurality of pages, in order that the throughput may improve,  
20 the scheduling task directs the engine controller 105 to perform printing while ordinarily instructing the option controller 106 to perform printing two or three pages ahead, whereby steps S702 to S708 are repeatedly executed before processing by the engine I/F task starts.

25 Although step S706 is branched depending on whether the

discharged paper is stacked on the selected discharging bin in the discharging-bin automatic-selection mode (in step S720 as shown in Fig. 12), the scheduling task may proceed to step S707 when the moved discharging bin is full, or may proceed to step S708 when the moved discharging bin is not full.

Fig. 8 is a flowchart illustrating an engine I/F task for executing printing based on page information created by the scheduling tasks shown in Figs. 7 and 12. Also the engine I/F task is executed by the video controller 103. The engine I/F task is activated at the print instruction from the scheduling task. The engine I/F task determines whether the scheduling task directs it to perform printing (step S801). If the engine I/F task has determined that the scheduling task directs it to perform printing, it monitors the laser beam printer 102 as to conditions (printing executable, paper size, etc.) and abnormal conditions (paper end, panel open, paper jam, etc.) (Step S802), and notifies a necessary task. The engine I/F task uses the engine I/F 406 to direct the engine controller 105 to perform printing, whereby printing is executed (step S803). The engine I/F task uses the option I/F 412 to notify the option controller 106 of a feeding start, a printing start, etc. (step S804) before returning to step S801.

Fig. 9 is a flowchart illustrating an option I/F task



for notifying the option controller 106 of information such as the condition of the page specified by the scheduling task, and reinstructions from the engine I/F task and other tasks. Also the option I/F task is executed by the video controller 103. In step S901, if a page instructed by the scheduling task to be printed is detected, the option I/F task monitors the condition of the page (step S902). At this time, if printed pages are detected, the option I/F task notifies the scheduling task of permission for eliminating the information. If a page instructed to be printed is not detected, the option I/F task does not monitor page condition but proceeds to step S903.

The option I/F task monitors the positions of the discharging bins, which are movable, (and whether the discharging bins are being moved) (step S903). The option I/F task monitors abnormal conditions such as paper end, paper jam, a full stack (step S904), and notifies a necessary task to perform operator call displaying, reinstruction executing, etc. In step S905, the option I/F task monitors and updates conditions such as the remaining amount of paper in the paper-feeding option unit 107, the stacked-paper amount of paper in the discharging option unit 108, and the remaining amount of staples. The option I/F task is notified of a reinstruction from the engine I/F task to determine whether reinstruction data is detected (step

S906). If the reinstruction data is detected, the option I/F task sends a reinstruction to the option controller 106, based on the reinstruction data (step S907), and the engine I/F task executes printing based on the reinstruction. The  
5 reinstruction is caused by a feeding system change due to paper end, and a discharging-bin change due to a full stack in discharging bin. The present instructions are switched.

Fig. 10 is a flowchart illustrating a user I/F task for notifying a user of a feeding and discharging system change caused by the reinstruction in accordance with remote  
10 control from panel operation and the host computer 101. Also the user I/F task is executed by the video controller 103.

In Fig. 10, when the user I/F task detects an  
15 instruction by panel operation or remote control from the host computer 101 (step S1001), it determines whether discharging-bin moving must be performed based on the instruction, which is different from the present bin instruction (step S1002). Only when discharging-bin moving  
20 is performed, light-emitting-diode or liquid-crystal-device indications related to the feeding and discharging system are changed (step S1003). The user I/F task notifies the host computer 101 of the feeding-and-discharging-bin change (step S1004).

25 In the foregoing embodiments, a discharging-bin change

has been described. However, similar processing may be performed for a movable feeding cassette, or a function in which another type of moving enables detection.

Although the above-described tasks are stored in the ROM 404, they may be down-loaded from the external unit 101 to a non-volatile RAM in the video controller 103, or they may be installed from a recording medium such as a floppy disc or a CD-ROM to the non-volatile RAM in the video controller 103.

As described above, in the case where a sheet stacking means is changed, a moving means moves the sheet stacking means and detection means detects the sheet-stacked condition of the sheet stacking means before image formation by image forming means is started. Thus, in a low-cost aimed image forming apparatus in which detection means detects the sheet-stacked conditions of a plurality of sheet stacking means, the above manner prevents defects generated when the stacked-paper amount of the selected sheet stacking means is controlled based on the previously detected results.